



## Technical Data

### Aluminium Textured Sheets

#### Introduction:

GA Axis & GA Vertex textured patterns are produced by an embossing process, from high quality aluminium materials, to Standard BS EN 485/515/573.

#### Material grades:

- Spec. 1050A – Good formability and anodising qualities.
- **Surface Finishes:**
- Natural Anodised
- Mill (untreated)
- Powder coated (on request)

#### Material Thickness:

- 1.0mm.

#### Notes:

Good surface on one side only : Flatness tolerances on patterned sheets do not apply.

Panel sizes can vary +/- 2% : With anodised items, shade variations can occur between sheets.

Jig/clamp marks are unavoidable on full size sheets, usually these are no more than 19mm in from the sheet edges/ends.

#### BS & European Standards and Specifications

Aluminium Sheet: BS EN BS EN 485/515/573

BS EN 485: Aluminium & Aluminium Alloy Sheet, strip, plate. Mechanical properties.

BS EN 515: Wrought products, temper designations.

BS EN 573: Chemical composition, form of wrought products

**Anodising:** BS EN ISO 7599

Anodising of aluminium and its alloys. General specifications for anodic oxidation coatings on aluminium.

**Paint & Powder Coating: BS 6496 (1984):**

Specification for powder organic coatings for application and stoving to aluminium alloy extrusions, sheet and pre-formed sections for external architectural purposes, and for the finish on aluminium alloy extrusions, sheet and preformed sections coated with powder organic coatings.

GA Helpline 020 8692 2255 Mon-Fri 8.30am-5pm for professional assistance  
[www.goodngalum.com](http://www.goodngalum.com) [sales@goodingalum.com](mailto:sales@goodingalum.com)

© Gooding Aluminium Limited