

Page 1 of 2

Installation

C Series Corner Protectors

Introduction:

Please read these instructions before using this product. If there is anything you do not understand or if you want to know more about these items, please contact GA.

C Series Corner Protectors should be installed by suitably qualified contractors with the required knowledge and expertise. Current standard construction methods must be used.

It is the responsibility of the contractor to ensure proper safety during and after completion of the installation, so that the corner protectors remain safely secured to the fixing surface.

Before beginning the installation, please refer to our Health & Safety data sheet, for guidance regarding Off-Loading, Site Storage, etc.

Please note that on anodised stock lengths, jig marks are normally visible at the extreme ends. These marks should be cut away before fixing commences.

Fixing:

Corner protectors are normally secured with a propriety adhesive to clean, stable, and level surfaces.



Above: In-situ plan view

Adhesives are to be applied in accordance with the manufacturer's instructions.

Wait until the adhesive is completely cured before cleaning away any dirt, grease etc., from the surface areas.



Page 2 of 2

Installation (ctd)

C Series Corner Protectors

Cleaning & Maintenance:

Regular housekeeping, and inspection are key to preserving the appearance and safety of Corner Protectors.

Frequent checks should be made to ensure that the corner protectors remain securely fitted and are maintained to remain so.

All that is normally required to maintain the appearance and prevent the build-up of surface contaminants on the surfaces, is by regularly wiping over with a soft cloth.

Any liquids being used for cleaning purposes must be applied in small amounts to a soft cloth. Greasy deposits can be removed with organic solvents, white spirit etc., followed by wiping over with a mild diluted detergent and rinsing with cold water. Dry off with a soft cloth.

It is important that abrasive cleaners or scourers are not used as they may damage the surface.